



# VRX Series

DIRECT DRIVE MOTOR - SAE J 609A



**G** | Ø 3/4"

**4.5oz**  
OIL CAPACITY  
(30w Non-Detergent)

MAX  
60°C  
140°F

**Built-In Unloader**

### HOLLOW SHAFT Ø 3/4"

Part #	Model	Version	Ø	🔧	📊	🔌	🏋️	⬇️	⬆️
			Piston	GPM	PSI	HP	LBS	Inlet	Outlet
6511.0020.00	VRX 2225	G	14mm	2.2	2500	4.0	8.0	3/4" FNH	M22 x 1.5 - M
6511.0005.00	VRX 2522	G	14mm	2.5	2200	4.2	7.3		
6511.0015.00	VRX 2524	G	14mm	2.5	2400	4.4	7.7		
6511.0025.00	VRX 2527	G	14mm	2.5	2700	5.1	7.7		
★ 6511.0033.00	VRX 2527	G7	14mm	2.5	2700	5.1	8.8		

★ Featuring 7/8" Cylindrical Hollow Shaft

### VRX SERIES REPAIR KITS

Part #	Kit Style	Description
5026.0256.00	<b>Seal</b>	Water, 2200+ PSI
5019.0668.00		Water, 2700+ PSI
5026.0257.00	<b>Valve</b>	Rebuild, (2225 & 2522 )
5026.0270.00		Rebuild, (2524 & 2527)
1215.0342.00		Regulator, Brass
5026.0260.00	<b>Piston</b>	Seals